



EXTERNAL BLINDS

ZF3000
ZF3000-BX



So that your house is "the best"

WWW.PORTOS.COMPANY


EXTERNAL BLINDS

ZF3000, ZF 3000-BX





THREE BOX HEIGHTS

The sizes of the 250 mm, 300 mm and 350 mm boxes are designed to optimally contain the package of external blinds while maintaining one universal depth of 148 mm.



OPTION OF THE BOX ON THE FACADE

Thanks to the specially designed extruded front profile, the box can be installed on the facade. Only available in box 250.



CAST ALUMINIUM SIDE AND EXTRUDED PROFILES

Thanks to the cast sides and extruded profiles, the system is distinguished by high rigidity and well-matched elements.

TWO OPTIONS OF THE FLUSH-MOUNTED BOX

The box has been designed so as to allow the use of additional rear two-centimetre insulation of the box in the case there is no withdrawal of the lintel, and the option adjacent directly to the wall in the case of already insulated wall. For each of the options, dedicated guides with or without a spacer are provided.



EASY ACCESS TO THE BOX

Each of the box options allows to open the inspection cover from the front of the box before plastering. Thanks to this solution, it will not be difficult to connect the blinds package or to adjust the end positions of the motor.

ALUMINIUM GUIDES FOR COMPLETE OR PARTIAL BUILDING-UP

Due to the variety of finishing designs, the guides have been designed in such a way as to ensure building them up completely or partially to enhance the color aesthetics. The package can be uninstalled thanks to the flexible PVC insert when the guides are completely built-up, or to the aluminium guide when the guides are partially built-up.



ZF3000-BX WITH MOSQUITO NET

When decided to buy the ZF3000-BX without mosquito net, nothing is lost because the box is designed so that a mosquito net can be added at any time. An independent mounting system with guides allows the addition of a mosquito net to the already existing ZF3000-BX.

COLORS

WHITE RAL 9016	BEIGE VSR 240	LIGHT GRAY RAL 7035	SILVER RAL 9006
STEEL ANTHRACITE DB 703	ANTHRACITE RAL 7016	DARK ANTHRACITE RAL 7021	GRAY ALUMINIUM RAL 9007
OLIVE VSR 780	BLACK RAL 9005		

UNIVERSAL BOX

Are you wondering what depth of the box to use? The ZF3000-BX has one universal depth for each type of external blind slats. The depth of 148 mm allows the box to be perfectly integrated into the building insulation.



C80

SHAPE OF THE SLATS	C
MAXIMUM WIDTH	4500 mm
MAXIMUM HEIGHT	5000 mm
MAXIMUM AREA	16 m ²
ELECTRIC DRIVE	YES
MANUAL DRIVE	YES
INSTALLATION - SETS	YES

Z90

SHAPE OF THE SLATS	Z
MAXIMUM WIDTH	4500 mm
MAXIMUM HEIGHT	5000 mm
MAXIMUM AREA	16 m ²
ELECTRIC DRIVE	YES
MANUAL DRIVE	YES
INSTALLATION - SETS	YES

ZF3000, ZF 3000-BX

THE CURRENT EXTERNAL BLIND SYSTEM, WHICH IS A MODERN AND ELEGANT PRODUCT CHANGING THE CHARACTER OF THE BUILDING, GAVE IT A MORE INTERESTING AND MODERN LOOK, BUT IT WAS QUITE DIFFICULT TO INSTALL. AFTER DEVELOPING THE PRODUCT AND LISTENING TO THE EXPECTATIONS OF CUSTOMERS, WE INTRODUCE THE ZF3000-BX SYSTEM AS A SYSTEM SOLUTION OF A COMPLETELY ASSEMBLED BLIND BOX INSTALLED ON ALUMINIUM GUIDES. HENCE, THE AESTHETICS OF BOXES FOR BLINDS IS INCREASED. THANKS TO THE CAST ALUMINIUM SIDES, WE STAND OUT FROM THE COMPETITION.

COMBINED WITH SOLID PRESSED BOX PROFILES AND DEDICATED GUIDES FOR THEIR COMPLETE OR PARTIAL BUILDING-UP, A SYSTEM WITH FAST AND COMFORTABLE INSTALLATION HAS BEEN DEVELOPED. THREE BOX HEIGHTS, WITH ONE DEPTH, ENSURE VERSATILITY OF THE EXTERNAL BLIND PROFILES APPLIED. SPECIALLY DESIGNED GUIDES ENSURE OPERATION OF C80 OR Z90 SLATS WITH AN OPTIONAL MOSQUITO NET. A GREAT ADVANTAGE OF OUR SOLUTION IS AN INDEPENDENT MOSQUITO NET SYSTEM, WHICH CAN BE ADDED AT ANY TIME TO AN ALREADY INSTALLED EXTERNAL BLIND BOX. THE ZF3000-BX HAS BEEN DEVELOPED TO PROVIDE VERY EFFICIENT INSTALLATION AND THE AESTHETICS AT EVEN HIGHER LEVEL THAN IN THE MARKET. ZF3000 EXTERNAL BLINDS IN THE ZF3000 -BX SYSTEM BOX PROTECT EVEN MORE THE INTERIOR OF THE BUILDING AGAINST EXCESSIVE SUNLIGHT, PROVIDING AN EFFECTIVE BARRIER ALLOWING TO MAINTAIN A STABLE TEMPERATURE IN THE ROOM. APPROPRIATE ADJUSTMENT OF THE INTERIOR DIMMING AND HEAT TRANSFER ARE PROVIDED BY THE CHANGE OF THE SLAT INCLINATION ANGLE. IN ADDITION, THEY EFFECTIVELY ELIMINATE EXCESSIVE NOISE.



DISTRIBUTOR



PORTOS TR7
spółka z ograniczoną odpowiedzialnością sp.k.



UL. ŻŁOTA 71
62-800 KALISZ
TEL. 62 768 40 00
sekretariat@portosrolety.pl
www.portos.company